PATENT APPLICATION TRANSMITTAL LETTER
(Large Entity)

Docket No.
END920000054US1

TO THE ASSISTANT COMMISSIONER FOR PATENTS

Transmitted herewith for filing under 35 U.S.C. 111 and 37 C.F.R. 1.53 is the patent application of:

Cesana et al.

For: **SECURITY CLOTH DESIGN AND ASSEMBLY**

Enclosed are:

- ☒ Certificate of Mailing with Express Mail Mailing Label No. **EL396832425US**
- ☒ 5 sheets of drawings.
- ☐ A certified copy of a application.
- ☒ Declaration ☒ Signed. ☐ Unsigned.
- ☒ Power of Attorney
- ☒ Information Disclosure Statement
- ☐ Preliminary Amendment
- ☒ Other: **Assignment and Assignment Cover Sheet**

CLAIMS AS FILED

For	#Filed	#Allowed	#Extra	Rate	Fee
Total Claims	31	- 20 =	11	x $18.00	$198.00
Indep. Claims	5	- 3 =	2	x $80.00	$160.00
Multiple Dependent Claims (check if applicable) ☐					$0.00
				BASIC FEE	$710.00
				TOTAL FILING FEE	$1,068.00

- ☐ A check in the amount of to cover the filing fee is enclosed.
- ☒ The Commissioner is hereby authorized to charge and credit Deposit Account No. **09-0457 (IBM)** as described below. A duplicate copy of this sheet is enclosed.
  - ☒ Charge the amount of **$1,068.00** as filing fee.
  - ☒ Credit any overpayment.
  - ☒ Charge any additional filing fees required under 37 C.F.R. 1.16 and 1.17.
  - ☐ Charge the issue fee set in 37 C.F.R. 1.18 at the mailing of the Notice of Allowance, pursuant to 37 C.F.R. 1.311(b).

Dated: Nov. 20, 2000

Lawrence R. Fraley
Signature

Lawrence R. Fraley
Reg. No. 26,885
IBM Corp. IP Law Dept. N50/040-4
1701 North Street
Endicott, NY 13760
(607) 755-3207

cc:

CERTIFICATE OF MAILING BY "EXPRESS MAIL" (37 CFR 1.10) Applicant(s): Cesana et al.	Docket No. END920000054US1

Serial No.	Filing Date	Examiner	Group Art Unit

Invention: **SECURITY CLOTH DESIGN AND ASSEMBLY**

I hereby certify that the following correspondence:

Patent Application and Corresponding Paperwork, IDS w/ References

(Identify type of correspondence)

is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 in an envelope addressed to: The Assistant Commissioner for Patents, Washington, D.C. 20231 on

11/20/00
(Date)

June M. Mitchell
(Typed or Printed Name of Person Mailing Correspondence)

June M. Mitchell
(Signature of Person Mailing Correspondence)

EL396832425US
("Express Mail" Mailing Label Number)

Note: Each paper must have its own certificate of mailing.

APPLICATION

FOR

UNITED STATES LETTERS PATENT

APPLICANT(S) NAME: Cesana et al.

TITLE: SECURITY CLOTH DESIGN AND ASSEMBLY

DOCKET NO. END920000054US1

INTERNATIONAL BUSINESS MACHINES CORPORATION

Certificate of Mailing Under 37 CFR 1.10

I hereby certify that, on the date shown below, this correspondence is being deposited with the United States Postal Service in an envelope addressed to the Assistant Commissioner for Patents, Washington, D.C., 20231 as "Express Mail Post Office to Addressee".

"Express Mail" Label Number EL396832425US

On 11/20/00

June M. Mitchell

Typed or Printed Name of Person Mailing Correspondence

June M. Mitchell 11/20/00

Signature of Person Mailing Correspondence *Date*

SECURITY CLOTH DESIGN AND ASSEMBLY

BACKGROUND OF THE INVENTION

Technical Field

The present invention relates generally to the detection of intrusions into security enclosures, and more particularly, to the assembly of a security enclosure capable of detecting intrusions.

Related Art

Security enclosures are commonly used in network electronics commerce to transmit encrypted information to authorized persons. Fig. 1 shows a related art security enclosure 8, comprising an electronic assembly 10, which typically comprises a cryptographic processor card within an enclosure, and a tamper respondent wrap or cloth 12. The cloth 12 adheres to the assembly 10 by an adhesive on the inner surface of the cloth 12. The cloth 12 typically consists of several layers of a flexible dielectric having electrical traces or lines (not shown) thereon. Damage to any of the traces within a layer produces a change in resistance which prompts the cryptographic processor card to erase the information stored therein.

As illustrated in Fig. 2, a first side of the cloth 12 is

wrapped around the assembly 10. An end 16 of the cloth 12 is inserted within an opening 14 of the assembly 10. The end 16 comprises a plurality of silver filled ink lines formed on the surface of the end 16 to provide an electrical connection between the cloth 12 and the assembly 10. Thereafter, a second end of the cloth 12 is wrapped around the assembly 10, covering the inserted end 16 and over-lapping the first end of the cloth 12 (Fig. 3).

Unfortunately, because the cloth 12 is constructed of multiple layers (not shown) of unreinforced organic dielectric materials which are dimensionally unstable, i.e., susceptible to deformation due to environmental changes, it is difficult to maintain layer-to-layer alignment. As a result, it is difficult to ensure that each layer of the cloth terminates at the end 16, which is necessary in order to make the proper connection with the assembly 10. Likewise, the silver coating at the end 16 is susceptible to electromigration problems, thereby resulting in potential device failure. Furthermore, because the adhesive material on the inner surface of the cloth 10 securely adheres the cloth 12 to the assembly 10 prior to inserting the end 16 into the assembly 10, alignment of the end 16 into the opening 14 of the assembly 10 is often difficult, particularly when the cloth 12 and assembly 10 are slightly misaligned. This may

result in device failure due to a poor connection between the end 16 of the cloth 12 and the assembly 10. Likewise, additional forces exerted on the connection over time due to thermal and mechanical stresses, may further weaken the poor connection producing device failure. Moreover, the process of folding the security cloth and inserting the end into the connector is not amenable to automation, thus increasing manufacturing costs. Accordingly, there exists a need in the industry for a security enclosure that solves these and other problems.

SUMMARY OF THE INVENTION

The first general aspect of the present invention provides a security enclosure, comprising: an electronic assembly; a tamper respondent wrap secured around the assembly; and an extension cable electrically connecting the cloth to the assembly.

The second general aspect of the present invention provides a security enclosure, comprising: an electronic assembly; an extension, having a first end inserted in the assembly, and a second end having at least one bonding pad thereon; and a tamper respondent wrap surrounding the assembly, having at least one corresponding bonding pad, wherein the bonding pad of the extension is secured to the bonding pad of the wrap.

The third general aspect of the present invention provides a

security enclosure, comprising: an electronic assembly; and a tamper respondent wrap electrically connected to the assembly via an attachable extension.

The fourth general aspect of the present invention provides a flexible extension for use in a security enclosure, comprising: a first end having a plurality of interconnections which are inserted within an electronic assembly of the enclosure; a second end having a plurality of bonding pads thereon which are secured to a tamper respondent wrap of the enclosure; and wherein the cable electrically connects the wrap and the assembly.

The fifth general aspect of the present invention provides a method of forming a security enclosure, comprising: providing an electronic assembly having an opening therein; inserting a first end of an extension within the opening of the assembly; wrapping a tamper respondent wrap at least partially around the assembly; and connecting a second end of the extension to the wrap.

The foregoing and other features of the invention will be apparent from the following more particular description of the embodiments of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

The embodiments of this invention will be described in

detail, with reference to the following figures, wherein like designations denote like elements, and wherein:

Fig. 1 depicts a cross-sectional view of a related art electronic assembly and tamper respondent cloth;

Fig. 2 depicts the related art assembly of Fig. 1 wherein the cloth is electrically connected to the assembly;

Fig. 3 depicts the related art assembly of Fig. 2 wherein the remainder of the cloth is secured around the assembly;

Fig. 4 depicts a cross-sectional view of an electronic assembly in accordance with the present invention;

Fig. 5 depicts the assembly of Fig. 4 and a tamper respondent cloth;

Fig. 6 depicts the assembly of Fig. 5 wherein bonding pads of the cloth and an extension cable are connected;

Fig. 7 depicts the assembly of Fig. 6 wherein the remainder of the cloth is secured around the assembly;

Fig. 8 depicts an enlarged top view of the extension cable in accordance with the present invention; and

Fig. 9 depicts an enlarged top view of the cloth bonding pads in accordance with the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Although certain embodiments of the present invention will

be shown and described in detail, it should be understood that various changes and modifications may be made without departing from the scope of the appended claims. The scope of the present invention will in no way be limited to the number of constituting components, the materials thereof, the shapes thereof, the relative arrangement thereof, etc. Although the drawings are intended to illustrate the present invention, the drawings are not necessarily drawn to scale.

Referring to the drawings, Fig. 4 shows a cross-sectional view of an electronic assembly 100 in accordance with the present invention. The assembly 100 typically comprises a cryptographic processor card 102 (shown in phantom), for the storage of key codes required to encrypt and decrypt the secured information, enclosed within a container 106, such as a metal box.

An extension cable 112 is inserted within an opening 114 of the assembly 100. The extension cable 112 comprises a polyimide dielectric material, such as Kapton™ (DuPont), Upilex™ (UBE), Mylar™ (DuPont), or other similar thin flexible dielectric material conventionally used in flex circuitry. In particular, a cable end 116 located at a first end of the extension cable 112 makes electrical connection with the cryptographic processor card 102 within the assembly 100. A plurality of bonding pads 118 located at a second end of the extension cable 112 makes

electrical connection with a cloth (described below). The bonding pads 118 are formed of copper, having a nickel/gold plating thereon, or other metals, such as silver, etc. The gold provides good conductivity, and the nickel prevents the diffusion of gold into the copper. Alternatively, the bonding pads 118 may be formed of an electrically conductive thermosetting polymer, or an electrically conductive thermoplastic polymer.

As illustrated in Fig. 5, a tamper respondent wrap or cloth 120 is wrapped around the assembly 100, such that a plurality of bonding pads 122 on the cloth 120 align with the plurality of bonding pads 118 on the extension cable 112. The cloth 120, such as disclosed in the patent to MacPherson (US 5,858,500), is a sheet of composite material comprising a laminate formed of a number of separate layers, including a delamination respondent layer, and a pierce and laser respondent layer. Each layer has a plurality of ink traces or lines (shown in Fig. 9) formed thereon, for the detection of intrusions. The lines may comprise an electrically conductive thermoplastic polymer, electrically conductive thermoset polymer, metal, etc. The cloth 112 further includes a pressure sensitive adhesive material 121 on the inner surface of the cloth 112, such that the cloth 112 securely adheres to the assembly 100. The bonding pads 122 are formed of copper, having a nickel/gold plating thereon, or other metals,

such as silver, etc. Alternatively, the bonding pads 122 may be formed of an electrically conductive thermosetting polymer, or an electrically conductive thermoplastic polymer.

As illustrated in Fig. 6, the bonding pads 118 of the extension cable 112 are secured to the bonding pads 122 of the cloth 120 to complete the electrical connection between the cloth 120 and the assembly 100. A thermal compression bonding (TCB) process may be used in which heat and pressure are applied to the bonding pads 118, 122 until the bonding pads 118, 122 begin to melt and bond together. A heater having the correct dimensions corresponding to the size of the bonding pads 118, 122, conventionally used in TCB processing, may also be used to apply heat and pressure directly to the bonding pads 118, 122. The specific range of temperatures and pressures necessary to bring the metals, or base polymers within the bonding pads 118, 122 to their melting point depends upon the materials selected, and is commonly known in the art.

The bonding pads 118, 122 may be bonded directly to one another using the TCB process described above if the bonding pads 118, 122 are formed of a conductive thermoplastic polymer. In the event the bonding pads 118, 122 are formed of a conductive thermoset polymer, or a metal, an additional conductive adhesive is needed between the bonding pads 118, 122 to bond the pads 118,

122 together. For instance, an anisotropic conductive tape, such as 3m 7303™ (3M), may be inserted between the bonding pads 118, 122 prior to performing the TCB process to form the adhesive connection therebetween.

Thereafter, the remaining portion of the cloth 120 is wrapped around the assembly 100, adhering to and covering the extension cable 112 and over-lapping the other end of the cloth 120 to form a tightly sealed enclosure 123 (Fig. 7). It should be noted that due to the flexible nature of the extension cable 112, the profile of the assembly 100 and cloth 120 is much smoother and flatter than the related art design. This is because a certain amount of slack is required in the cloth of the related art design in order to insert and bend the stiff multiple layers of the cloth, which is not required with the flexible extension cable 112.

Figs. 8 and 9 show greater detail of the extension cable 112 and bonding pads 122 of the cloth 120, respectively, in a top view. In particular, the cable end 116 at a first end of the extension cable 112 includes a plurality of interconnections 124 that mate with and form an electrical connection with the cryptographic processor card 102 inside the assembly 100. The interconnections 124 are formed of copper with a nickel/gold plating, or other similarly used material. Each bonding pad 118

has a corresponding interconnection 124. Wires 126 connect each bonding pad 118 with an interconnection 124.

Each bonding pad 122 formed on the first end of the cloth 120 corresponds to the location of, and aligns with, each bonding pad 118 of the extension cable 112. In this example, the cloth 120 comprises a first or top layer 128 and a second or bottom layer 130. As illustrated, the top layer 128 is partially cut away to remove section 131, thereby exposing the bottom layer 130 for connection to the extension cable 112.

In this example, the top layer 128 of the cloth 120, for instance, the pierce and laser respondent layer, has three bonding pads 122a associated therewith. A system of connections 132, particularly a plurality of resistors formed in parallel and/or series, run throughout the layer 128, (a schematic representation of which is illustrated in Fig. 9), and connect the traces 125 within the layer 128 to the bonding pads 122a. Similarly, the bottom layer 130, for instance, the delamination respondent layer, has three bonding pads 122b associated therewith. A system of connections 134, particularly a plurality of resistors formed in parallel and/or series, run throughout the layer 130, (a graphic representation of which is illustrated in Fig. 9), and connect the traces 125 within the layer 130 to the bonding pads 122b.

A change in resistance within the system of connections 132, 134 indicates a break or short in the traces 125 within the respective layers 128, 130, e.g., caused by an attempted break-in. This change in resistance is detected as a change in voltage drop across the resistor network, which is then relayed to the corresponding bonding pads 122a, 122b of the cloth 120. The bonding pads 122a, 122b, in turn relay the change in voltage drop to the corresponding bonding pads 118 of the extension cable 112, which then transfers the message through wires 126 and interconnections 124 to the cryptographic processor card 102. Thereafter, the cryptographic processor card 102 may take the appropriate precautions to prevent the information from being divulged, such as erasing the stored key codes for encrypting and decrypting the secured information.

The extension cable 112 provides for easier connection of the cloth 120 to the assembly 100 than with conventional techniques. This is particularly true due to the small size and tight tolerances of the assembly opening 114 and the interconnections 124. The extension cable 112 also provides a surface large enough to facilitate an automated assembly process. Likewise, because the interconnections 124 are formed on the extension cable 112 rather than on the end of the cloth 120, the cable end 116 can be inserted in the opening 114 of the assembly

100 without first adhering the cloth 120 to the assembly 100. This reduces the problems associated with proper placement and alignment of the cloth 120. Also, due to the flexible nature of the extension cable 112, slight misalignment of the cloth 120 can be compensated for when the extension cable 112 is connected to the cloth 120. In fact, misalignment of several millimeters may be tolerable between the bonding pads 118, 122. Furthermore, because the interconnections 124 are formed of copper with a nickel/gold plating, rather than silver ink, the electromigration problems are minimized.

It should be noted that the embodiments disclosed above are not intended to limit the scope of the present invention in any way. For instance, the cloth 120 may be formed of more or less layers than that of the cloth 120 described herein. In which case, a system of connections and corresponding bonding pads would be needed for each layer. Furthermore, the number of bonding pads on each layer, and the corresponding bonding pads on the extension cable, may be varied as needed.

While this invention has been described in conjunction with the specific embodiments outlined above, it is evident that many alternatives, modifications and variations will be apparent to those skilled in the art. Accordingly, the embodiments of the invention as set forth above are intended to be illustrative, not

limiting. Various changes may be made without departing from the spirit and scope of the invention as defined in the following claims.

CLAIMS

We claim:

1. A security enclosure, comprising:

an electronic assembly;

a tamper respondent wrap secured at least partially around the assembly; and

an extension cable electrically connecting the wrap to the assembly.

2. The security enclosure of claim 1, wherein the electronic assembly comprises a cryptographic processor card.

3. The security enclosure of claim 1, wherein the tamper respondent wrap includes an adhesive inner surface that adheres the wrap to the electronic assembly.

4. The security enclosure of claim 1, wherein the tamper respondent wrap further includes a plurality of bonding pads formed at a first end of the wrap.

5. The security enclosure of claim 4, wherein the tamper respondent wrap further includes a system of resistors within each layer of the wrap.

6. The security enclosure of claim 5, wherein the system of resistors connect ink traces within each layer of the wrap to the bonding pads.

7. The security enclosure of claim 1, wherein the extension cable further includes a plurality of interconnections at a first end of the extension cable.

8. The security enclosure of claim 7, wherein the extension cable further includes a plurality of bonding pads at a second end of the extension cable.

9. The security enclosure of claim 8, wherein wires connect the interconnections and the bonding pads of the extension cable.

10. The security enclosure of claim 1, wherein a plurality of bonding pads on the wrap are bonded to a plurality of bonding pads on the extension cable.

11. The security enclosure of claim 10, wherein a thermal compression bonding process bonds the bonding pads on the wrap to the bonding pads on the extension cable.

12. The security enclosure of claim 1, wherein the wrap at least partially covers the extension cable.

13. The security enclosure of claim 1, wherein the extension cable comprises a flexible dielectric material.

14. A security enclosure, comprising:

an electronic assembly;

an extension, having a first end inserted in the assembly, and a second end having at least one bonding pad thereon; and

a tamper respondent wrap at least partially surrounding the assembly, having at least one corresponding bonding pad, wherein the bonding pad of the extension is secured to the bonding pad of the wrap.

15. The security enclosure of claim 14, wherein the first end of the extension comprises at least one interconnection which forms an electrical connection between the assembly and the extension.

16. The security enclosure of claim 15, wherein the at least one interconnection is electrically connected to the at least one bonding pad of the extension via a wire.

17. The security enclosure of claim 14, wherein the wrap further includes an adhesive on an inner surface of the wrap to secure the wrap to the assembly.

18. The security enclosure of claim 14, wherein the wrap further includes a system of resistors connecting ink traces within the wrap to the bonding pads of the wrap.

19. The security enclosure of claim 14, wherein the extension comprises a flexible cable.

20. A security enclosure, comprising:

an electronic assembly; and

a tamper respondent wrap electrically connected to the assembly via an attachable extension.

21. The security enclosure of claim 20, wherein the attachable extension comprises a flexible extension cable.

22. The security enclosure of claim 20, wherein the tamper respondent wrap comprises a plurality of bonding pads formed on an end thereof.

23. The security enclosure of claim 21, wherein the extension comprises a plurality of bonding pads formed on a first end thereof.

24. The security enclosure of claim 23, wherein the bonding pads of the wrap are secured to the bonding pads of the extension.

25. The security enclosure of claim 23, wherein the extension further comprises a plurality of interconnections formed at a second end of the extension.

26. The security enclosure of claim 22, wherein a system of resistors electrically connects the bonding pads of the wrap to ink traces of the wrap.

27. The security enclosure of claim 24, wherein the bonding pads of the wrap are secured to the bonding pads of the extension using a thermal compression bonding process.

28. A flexible extension for use in a security enclosure, comprising:

a first end having a plurality of interconnections which are inserted within an electronic assembly of the enclosure;

a second end having a plurality of bonding pads thereon which are secured to a tamper respondent wrap of the enclosure; and

wherein the cable electrically connects the wrap and the assembly.

29. The flexible extension of claim 28, wherein the bonding pads of the extension are bonded to bonding pads of the wrap.

30. The flexible extension of claim 28, wherein the extension comprises a dielectric material.

31. A method of forming a security enclosure, comprising:

providing an electronic assembly having an opening therein;

inserting a first end of an extension within the opening of the assembly;

wrapping a tamper respondent wrap at least partially around the assembly; and

electrically connecting a second end of the extension to the wrap.

SECURITY CLOTH DESIGN AND ASSEMBLY

ABSTRACT OF THE DISCLOSURE

The present invention provides a security enclosure having an electronic assembly, such as a cryptographic processor card enclosed within an enclosure, surrounded by a tamper respondent wrap. The enclosure further includes a flexible extension cable which electrically connects the wrap and the assembly. The extension cable includes a plurality of interconnections at a first end to form an electrical connection with the assembly, and a plurality of bonding pads at a second end to form an electrical connection with a plurality of corresponding bonding pads of the wrap.



FIG. 1 (RELATED ART)



FIG. 2 (RELATED ART)



FIG. 3 (RELATED ART)



FIG. 4



FIG. 5



FIG. 6



FIG. 7



FIG. 8



FIG. 9

Docket No.
END920000054US1

Declaration and Power of Attorney For Patent Application

English Language Declaration

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

SECURITY CLOTH DESIGN AND ASSEMBLY

the specification of which

(check one)

☒ is attached hereto.

☐ was filed on _____ as United States Application No. or PCT International Application Number _____

and was amended on _____

(if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose to the United States Patent and Trademark Office all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119(a)-(d) or Section 365(b) of any foreign application(s) for patent or inventor's certificate, or Section 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate or PCT International application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)			Priority Not Claimed
_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	☐
_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	☐
_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	☐

I hereby claim the benefit under 35 U.S.C. Section 119(e) of any United States provisional application(s) listed below:

(Application Serial No.)	(Filing Date)

I hereby claim the benefit under 35 U. S. C. Section 120 of any United States application(s), or Section 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. Section 112, I acknowledge the duty to disclose to the United States Patent and Trademark Office all information known to me to be material to patentability as defined in Title 37, C. F. R., Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application:

(Application Serial No.)	(Filing Date)	(Status) (patented, pending, abandoned)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. *(list name and registration number)*

David L. Adour - 29,604
Lawrence R. Fraley - 26,885
John R. Pivnichny - 43,001
Arthur J. Samodovitz - 31,297
William H. Steinberg - 28,540
Christopher A. Hughes - 26,914
Edward A. Pennington - 32,588
John E. Hoel - 26,279
Joseph C. Redmond, Jr. - 18,753

Send Correspondence to: **Customer No. 5409**

Direct Telephone Calls to: *(name and telephone number)*
Kristen L. Ashdown - (518) 220-1850

Full name of sole or first inventor **Mario L. Cesana**	
Sole or first inventor's signature	Mario L. Cesana 11/3/2000 Date
Residence **Via C: Guidino 42/E, 20045 Besana in Brianza, Milano, Italy**	
Citizenship **Italian**	
Post Office Address **Same as Residence**	

Full name of second inventor, if any **Donald S. Farquhar**	
Second inventor's signature	Donald S Farquhar 11/17/2000 Date
Residence **1106 Rodman Road, Endicott, NY 13760**	
Citizenship **USA**	
Post Office Address **Same as Residence**	

Full name of third inventor, if any
Martino Taddei

Third inventor's signature Martino Taddei Date 11/3/2000

Residence
Donizetti, 19, Merate, Italy

Citizenship
Italian

Post Office Address
Same as Residence

Full name of fourth inventor, if any

Fourth inventor's signature Date

Residence

Citizenship

Post Office Address

Full name of fifth inventor, if any

Fifth inventor's signature Date

Residence

Citizenship

Post Office Address

Full name of sixth inventor, if any

Sixth inventor's signature Date

Residence

Citizenship

Post Office Address